TABLE 02-A: SINGLE-FAMILY RESIDENTIAL DEVELOPMENT STANDARDS

For exceptions and explanatory descriptions of these standards and for other development standards that apply to single-family residential areas, see Articles VI and VII of this title. The number which follows an "RS-" designation indicates the maximum number of lots per acre permitted in the zone; the "RS-A" number indicates the minimum number of acres per lot permitted.

	RS-4 RS-4 RS-5								
RS-5	RS-4	RS-3	RS-2	RS-1	RS-A5			DISTRICT	
8,000 sf	10,000 sf	13,000 sf	20,000 sf	l acre	5 acres		AREA	LOT DIMENSIONS ¹	
65	75	80	90	100	200		WIDTH DEPTH		
100	100	110	120	150	300				
20	20	20	20	20	20		FRONT		
20	20	20	20	25	30	TTL BOTH SIDES	INTERIOR SIDE	MINIMUM SETBACKS ^{3,6} FOR CITY CREATED LOTS	
10	10	10	10	10	10	ONE SIDE			
20	20	20	20	20	20		STREET SIDE	ACKS ^{3,6} 3D LOTS	
15	15	15	20	20	20		REAR		
20	20	20	20	20	20		FRONT	FOF INCO	
5	5	5	5	5	٠.		INTERIOR SIDE	MINIMUM SETBACKS ^{2,3,6} FOR LOTS CREATED PRIOR TO INCORPORATION / ANNEXATION	
01	0.1	10	10	10	10		STREET SIDE	BACKS ^{23,6} ED PRIOR T ANNEXATIO	
15	15	15	15	15	15		REAR		
52%	50%	45%	40%	25%	6%		*	MAXIMUM LOT COVERAGE	
16	16	16	16	16	16			MAXIMUM PARKING LOT HEIGHT ^{3,4,7} REQUIREMENT ⁵	
	less than 5,000 s.f. of habitable space = 2 enclosed garage spaces 5,000 s.f. or more of habitable space = 3 enclosed garage spaces								

94

For an existing lot which does not meet these standards, see Chapter 17.84 (Nonconformities). Lots of record, existing as of November 25, 1975 (adoption of this code), or within Eastview and existing as of January 5, 1983 (annexation), shall use these development standards for minimum

P :-

- ω. 4. For a description of height measurement methods and the height variation process, see Section 17.02.040 of this chapter. A height variation application shall be referred directly to the planning For description, clarification and exceptions, see Chapter 17.48 (Lots, Setbacks, Open Space Area and Building Height).
- A. Any portion of a structure which exceeds sixteen (16) feet in height extends closer than twenty-five (25) feet from the front or street-side property line.

 B. The area of the structure which exceeds sixteen (16) feet in height (second story footprint) exceeds seventy-five percent (75%) of the existing first story footprint area (residence and garage); commission for consideration, if any of the following is proposed:

- C. Sixty percent (60%) or more of an existing garage footprint is covered by a structure which exceeds sixteen (16) feet in height (a second story).

 D. The portion of a structure that exceeds sixteen feet in height is being developed as part of a new single-family residence; or

 E. Based on an initial site visit, the director determines that any portion of a structure which is proposed to exceed sixteen (16) feet in height may significantly impair a view as defined in this
- 7.5 For parking development standards, see Section 17.02.030(B) of this chapter.

 A garage with direct access driveway from the street of access shall not be less than twenty feet from the front or street-side property line, which ever is the street of access. Exterior stairs to an upper story are prohibited, unless leading to and/or connected to a common hallway, deck or entry rather than a specific room.